

Recommended Actions for Cleaning

1. Sweep up loose dirt and debris. Set up caution signs if required.
2. Mix and dispense detergent diluted in water per manufacturer's instructions.

For use with Silikal® flooring, the following recommendations are made by:

- Ecolab recommends using **Oasis 115 XP** | Ph. 651-293-2233
- Diversey recommends using **Profi** | Ph. 800-558-2332 - avail. nationwide through W.W.Grainger

3. Scrub with deck brush or the **Silikal® Heavyweight system** | Ph. 888-830-1404
4. Rinse per recommendation of detergent manufacturer.
5. Squeegee off excess water to drain or vacuum with wet-vac system. Allow floor to dry.
6. If the cleaner has left a cloudy residue, it can be removed by using vinegar rinse.
30:1 water to vinegar solution will remove residue or film left by an all purpose cleaner.

Subject to budget, personnel and space limitations, other automated systems can be used:

- Omniflex Dispense & Vac by Kaivec Ph. 800-287-1136 - www.kaivac.com
- Diversey Taski Floor Cleaning Equipment Ph. 262-631-4001 - www.taskibydiverse.com

* HARMFUL ACTIONS TO AVOID

Solids or liquids above 185° degrees fahrenheit to come in contact with the floor.

Full strength bleach to come in contact with the floor.

Solvents to come in contact with the floor (E.g. oven / stove cleaner).

*Failure to adhere to and/or comply potentially voids all associated warranty obligations.

Silikal America

609-B Fertilla Street
Carrollton GA, 30117

770.830.1404

888.830.1404

www.silikalamerica.com

770.830.9213

info@silikalamerica.com

